



ANAND MEDICAIDS PRIVATE LIMITED

An ISO 13485:2003 & 9001:2000 Certified Company

CE
0434

HIGH VACUUM SUCTION UNITS ◀

HI-VAC PLUS (90 LTR / MIN)



Anand's High Vacuum - High Flow Suction Unit

Housing: Plastic moulded cabinet

Capacity: -700 mm Hg \pm 10 mm regulable, flutter free vacuum control knob, 90 ltrs / min

Pump Type: Double piston pump

Jars: 2 x 2.5 ltr. wide mouthed (Polycarbonate) with changeover lever. Provided with handle for hygiene while emptying / cleaning, safety jar with mechanical / electronic overflow motor shut off system and autoclavable bacterial filter.

Tubing: 10 mm ID x 2 mtr. (PVC)

Vacuum Gauge: Bourden type 6.25 cm dia 0-760 mm Hg calibration.

Power: 220 V, 50 Hz, Single Phase

Noise Level: 60 dB A \pm 3

Dimension & Weight: 46 x 32 x 86 cms, 22 Kg.



ANAND MEDICAIDS PRIVATE LIMITED

An ISO 13485:2003 & 9001:2000 Certified Company

CE
0434

HIGH VACUUM SUCTION UNITS ◀

MAGNAVAC



Anand's High Vacuum Suction Unit For Lipo Surgery

Housing: Stainless steel cabinet with pump cooling system

Capacity: -700 mm Hg \pm 10 regulable, flutter free vacuum control knob, 65 Ltrs / min.

Pump Type: Double rotary vane pump

Jars: Wide mouthed 2 x 2 Ltrs. (Polycarbonate) with self sealing bungs and mechanical overflow safety device.

Tubing: 10 mm ID x 2 mtr (PVC)

Vacuum Gauge: Bourden type 10 cm . Dia. 0-760 mm Hg calibration.

Power: 230 V, 50 Hz, 4 \pm 0.5 Amps, 430 watts. (110 V on request)

Noise Level: 50 dB A \pm 3.

Dimension & Weight: 50 x 38 x 70 cms, 40 kg